

TOP SECRET

DATA CENTER OPERATIONS BRANCH

NDS OPERATIONS PROCEDURE MANUAL
NO. P-I016

APPLICATIONS SOFTWARE
07 October 1985

IMAGE MOTION SENSING (IMS)
PROCESSING

SYMBOLIC TITLE: IMS
PROGRAMMER:

25X1

25X1

TOP SECRET

TOP SECRET**CLASSIFICATION**

DOCUMENT CHANGE REQUEST (DCR)		DCR NO: <u>0032</u> DATE LOGGED: <u>9/25/85</u> DATE CLOSED: <u>10/15/85</u>									
TITLE <u>IMAGE MOTION SENSING (IMS) PROCESSING</u>		NO. <u>P-I016</u>									
INITIATOR 	SECTION <u>APS</u>	(IF NEW, ASSIGNED BY CIB/DOC) 25X1 DATE PHONE 25X1									
TECHNICAL MONITOR 	SECTION 	DATE 	PHONE 								
SYSTEM AFFECTED: <u>X</u> 1100/OPS 1100/M&A <u> </u> COINS <u> </u> RTMS <u> </u> OTHER 25X1											
BRANCH CHIEF SIGNATURE 		DATE <u>25 Sep 85</u>									
INITIATING DOCUMENT NO.: DR # <u> </u> RFC # <u>R0774-3</u> OTHER <u> </u>											
NEED FOR CHANGE: RFC <u>R0774-3</u> Task <u>3</u>											
DCOB INTERIM APPROVAL: <table style="width: 100%; margin-top: 10px;"> <tr> <td style="width: 40%; vertical-align: top;"> <div style="border: 1px solid black; width: 100%; height: 100%;"></div> </td> <td style="width: 20%; text-align: center;"> DATE <u>9/30/85</u> </td> <td style="width: 20%; text-align: center;"> CONCUR <u>X</u> </td> <td style="width: 20%; text-align: center;"> NON-CONCUR <u> </u> </td> </tr> </table>				<div style="border: 1px solid black; width: 100%; height: 100%;"></div>	DATE <u>9/30/85</u>	CONCUR <u>X</u>	NON-CONCUR <u> </u>				
<div style="border: 1px solid black; width: 100%; height: 100%;"></div>	DATE <u>9/30/85</u>	CONCUR <u>X</u>	NON-CONCUR <u> </u>								
FINAL APPROVAL: <table style="width: 100%; margin-top: 10px;"> <tr> <td style="width: 40%; vertical-align: top;"> <div style="border: 1px solid black; width: 100%; height: 100%;"></div> </td> <td style="width: 20%; text-align: center;"> DATE <u>25 Sep 85</u> </td> <td style="width: 20%; text-align: center;"> CONCUR <u>✓</u> </td> <td style="width: 20%; text-align: center;"> NON-CONCUR <u> </u> </td> </tr> <tr> <td style="vertical-align: top;"> ED: C/OD: </td> <td style="text-align: center;"> DATE <u>10/7</u> </td> <td style="text-align: center;"> CONCUR <u>✓</u> </td> <td style="text-align: center;"> NON-CONCUR <u> </u> </td> </tr> </table>				<div style="border: 1px solid black; width: 100%; height: 100%;"></div>	DATE <u>25 Sep 85</u>	CONCUR <u>✓</u>	NON-CONCUR <u> </u>	ED: C/OD: 	DATE <u>10/7</u>	CONCUR <u>✓</u>	NON-CONCUR <u> </u>
<div style="border: 1px solid black; width: 100%; height: 100%;"></div>	DATE <u>25 Sep 85</u>	CONCUR <u>✓</u>	NON-CONCUR <u> </u>								
ED: C/OD: 	DATE <u>10/7</u>	CONCUR <u>✓</u>	NON-CONCUR <u> </u>								

TOP SECRET**CLASSIFICATION**

TOP SECRET

TABLE OF CONTENTS

	<u>Page</u>
1.0 SUMMARY	1
1.1 Introduction.....	1
1.2 References	2
1.3 Processing	2
2.0 OPERATIONAL FLOW CHART	4
3.0 COMPUTER RUN PREPARATION	5
3.1 Program Loading	5
3.2 Final Check Summary	5
3.3 Normal Run Instructions	5
3.4 Abnormal Run Instructions	7
3.5 Punched Card Input	8
3.6 Magnetic Tape Input	10
3.7 Magnetic Tape Output	11
3.8 High Speed Printer Output	12
4.0 ON-LINE COMPUTER PROCESSING	12
4.1 Equipment Requirements	12

TOP SECRET

TOP SECRET**1.0 SUMMARY****1.1 Introduction**

This procedure manual sets forth guidelines and information necessary for operations personnel in the handling of IMS processing. IEPD personnel require IMS data for accurate measurement of ICS imagery. There will be a printer listing generated of each IMS data message received. There may or may not be an IMS data message (R714) sent for every imaging pass, but no more than one R714 will be generated for each pass. The listing will be printed in the computer room, collated as received, and available for pickup each day by IEPD.

Definitions of terms used within this procedure are as follows:

- a. DTX11 - Runstream initiated by the Communication Symbiont Processor (C/SP) upon receipt of an IMS message from the external communications line DLT001.
- b. I(IS)(PS) - For any given R714 received by NDS, a runstream is started by the ESDRIVER software for a particular imaging satellite (IS) and pass (PS). (EXAMPLE I0104)
- c. MD - Mission Director, 25X1
- d. T - Suffix on REC or REF ID numbers when a test is being run.

Operations Control Officers, computer operators, and shift supervisors are responsible for complying with this procedure manual. The OCO is the final authority on IMS processing action on the NDS.

Specific Responsibilities:

- a. ESG/IEPD:
 - 1) IEPD is responsible for logging which messages are received of those expected.
 - 2) IEPD is responsible for retaining IMS printouts.
 - 3) IEPD is responsible for detecting data content errors and notifying the originator that these errors have occurred.
- b. OCO:

If the OCO is informed by MD or other cognizant personnel at that IMS data message will not be received, the OCO will notify IEPD. 25X1

TOP SECRET

TOP SECRET**1.2 References**

None

1.3 Processing

- a. Software Summary
 - The IMS data message (R714), via the C/SP, initiates the DTX11 runstream. The DTX11 runstream starts up ESDRIVER which reads, validates, and logs the message and starts up the I(IS)(PS) runstream. The I(IS)(PS) runstream initiates IMSLST which produces the output listing. The listing from the program is to be collated as received and saved for pickup by IEPD each day.
- b. Media Used - Automatic start up via I(IS)(PS) runstream.
- c. Equipment Requirements
 - Univac 1100
 - No special files will be created, with the exception of the normal print file XMS*IMS-PRINT, which is automatically maintained. Default size of print file is 128 tracks.
- d. Normal Run Instructions
 - IMSLST will normally be started up by the I(IS)(PS) runstream. ESDRIVER will provide the correct XCH*D1NNNN file name.
- e. Error & Recovery Routines
 - IMSLST can be restarted by starting up the XMS*C-RUNIMSISPS runstream as long as the appropriate XCH*D1NNNN message is still available. (See section 3.4)
- f. Expected Output
 - A printer listing 'I(IS)(PS)' will be generated every time a R714 message is received. This listing is a formatted translation of the R714 data message. This listing should be saved for pickup by IEPD personnel.
- g. Special Test Conditions
 - If the NDS receives a test message, a DTX11 runstream is initiated. This runstream catalogues a file for the message, XCH*D1SSN#, and starts ESDRIVER. ESDRIVER will send a display to the console including the message number, the character following the message number which specifies a test, and a brief note requesting that the OCO be informed of the receipt.

TOP SECRET

25X1


TOP SECRET

- The OCO shall inform ED/SPB that a test message has been received. ED/SPB will advise either to save to tape, list or delete the message. The "DLB/DLC DELETE" runstream should not be started until the OCO has been contacted.

TOP SECRET

TOP SECRET

2.0 OPERATIONAL FLOW CHART

**TOP SECRET**

TOP SECRET

3.0 COMPUTER RUN PREPARATION

3.1 Program Loading

No manual intervention is necessary. It is kicked off automatically by ESDRIVER.

Type of Program: Batch

Start Keyin: N/A

Run ID: IMSLST

DMR ID: N/A

3.2 Final Check Summary

N/A

3.3 Normal Run Instructions

IMSLST will normally be started up via the IISPS runstream. ESDRIVER will provide the correct XCH*D1NNNN file name.

Initiation: No operator intervention

Step by Step: N/A

TOP SECRET

TOP SECRET**3.3 Normal Run Instructions (Continued)****Messages:**

<u>Message</u>	<u>Cause</u>	<u>Operator Action</u>
N/A		

TOP SECRET

3.3 Normal Run Instructions (Continued)

Restart: No Restart is required under normal conditions.

Termination: N/A

Take-down: N/A

Disposition of Data: Save output listing 'IISPS' for IEPD

3.4 Abnormal Run Instructions

Messages: Diagnostic messages will be printed on the printer.

<u>Message</u>	<u>Cause</u>	<u>Operator Action</u>
'IMSLST ABNORMAL TERMINATION' 'SAVE ALL LISTINGS'	Bad Data in R714	Print both IMSLST print-files associated with this IS & PASS. Notify OCO. No corrective action can be made to the R714. OCO can call G.C. at <div data-bbox="1045 1129 1127 1171" style="border: 1px solid black; width: 50px; height: 20px; display: inline-block;"></div> and request a retransmission. If the problem still persists, save all listings and notify APS.
'ACT READ ERROR 1' 'ACT READ ERROR 2' 'NUMBER OF IMAGE RECORDS 'EXCEEDS RANGE NNNNN' 'READ IMAGE ERROR 1' 'READ IMAGE ERROR 2' 'SAMPLE PAIRS VALUE EXCEEDS RANGE NNNNN' 'READ SAMP ERROR 1' 'READ SAMP ERROR 2' 'ACT EOF' 'IMAGE EOF' 'SAMP EOF'	Bad Data in R714	No operator response necessary. Printer listing messages will be used by APS personnel to determine what action will be required. Source code is in XMS*P\$SYN.IMSLST.

If a request is received from IEPD to re-run a particular R714, the
Recovery Procedure can be exercised. (See Attachment A.)

3.5 Punched Card Input

Description:

N/A

TOP SECRET

3.5 Punched Card Input (Continued)

Sample Card Deck:

N/A

TOP SECRET

TOP SECRET

3.5 Punched Card Input (Continued)

Disposition: N/A

3.6 Magnetic Tape Input

Originator: N/A

Type of Unit: N/A

Standard Tape Label: N/A

Label Block File Name: N/A

Density: N/A

Code: N/A

Record and Block Size: N/A

File Sequence: N/A

Source Tape: N/A

Disposition: N/A

Restrictions: N/A

Quantity: N/A

TOP SECRET

3.7 Magnetic Tape Output

Type of Unit: N/A

Standard Tape Label: N/A

Label Block File Name: N/A

Density: N/A

Code: N/A

Record and Block Size: N/A

File Sequence: N/A

Disposition: N/A

Retention Period: N/A

Restrictions: N/A

Quantity: N/A

3.8 High-Speed Printer Output

Identification: IISPS

Type of Form: Standard

Disposition: There will normally be one listing to be printed (XMS*X-IMSXXXISPS). This listing will be picked up by IEPD. In cases where an abnormal situation might occur, an additional listing (IISPS) will be printed for APS personnel.

4.0 ON-LINE COMPUTER PROCESSING

4.1 Equipment Requirements

Computer: Univac 1100/80

Schema Used: None

Restrictions: None

Files Accessed: Program absolute: XMS*P\$ABS.IMSLST

Files Created/Deleted: XMS*X-IMSXXXISPS.

File Size:

IMSLST RECOVERY PROCEDURE

Approved For Release 2008/02/12 : CIA-RDP94T00858R000601490001-9